

Típus adatok

típus	gyártás	motorkód	szelepek	henger	Nm/RPM	térfogat	LE/RPM	üzemanyag rendszer	Furat	Löklet	motorlaj	kompreszió	s rítés	üzemanyag	el gyújtás
Audi 80/90 (B3)															
Audi 80 1.6	1986-1991	PP	8	4	140/2500	1595	70/5200	Pierburg 2EE	81,0	77,4	5W-40 vagy 10W-50	min. 7bar, norm. 12bar		95	18 fok
Audi 80 1.6	1986-1987	RN	8	4	120/2500	1595	75/5200	Keihin I.	81,0	77,4	5W-40 vagy 10W-50	min. 7bar, norm. 12bar		95	18 fok
Audi 80 1.6	1986-1987	RNA	8	4	120/2500	1595	70/4500	Keihin I.	81,0	77,4	5W-40 vagy 10W-50	min. 7bar, norm. 12bar			18 fok
Audi 80 1.6D	1986-1989	JK	8	4	100/2500	1588	54/4800	Bosch adagoló	76,5	86,4	5W-50 vagy 10W-50	min. 26bar, norm. 34bar	23,0:1		-
Audi 80 1.6D	1986-1989	JKA	8	4	100/2500	1588	50/4800	Bosch adagoló	76,5	86,4	5W-50 vagy 10W-50	min. 26bar, norm. 34bar	23,0:1		-
Audi 80 1.6TD	1986-1989	RA	8	4		1588	80	Bosch adagoló	76,5	86,4	5W-50 vagy 10W-60	min. 26bar, norm. 34bar	23,0:1		-
Audi 80 1.6TD	1987-1991	SB	8	4		1588	80	Bosch adagoló	76,5	86,4	5W-40 vagy 10W-60	min. 26bar, norm. 34bar	23,0:1		-
Audi 80 1.8	1986-1991	DZ	8	4		1781	112/5800	K-Jetronic	81,0	86,4	5W-40 vagy 10W-50	min. 7.5bar, norm. 10-13bar			6 fok
Audi 80 1.8	1986-1991	PV	8	4	155/3250	1781	110	KE-Jetronic	81,0	86,4	5W-40 vagy 10W-40	min. 7.5bar, norm. 10-13bar	10:1	95	6 fok
Audi 80 1.8	1986-1991	JN	8	4		1781	90/5400	KE-Jetronic	81,0	86,4	5W-40 vagy 10W-40	min. 7bar, norm. 9-12bar		95	6 fok
Audi 80 1.8	1986-1988	JV	8	4		1781	90/5200	Keihin	81,0	86,4	5W-40 vagy 10W-40	min. 7bar, norm. 9-12bar			7 fok
Audi 80 1.8	1986-1991	NE	8	4		1781	90/5200	Keihin I.	81,0	86,4	5W-40 vagy 10W-50	min. 7bar, norm. 9-12bar			10 fok
Audi 80 1.8	1986-1990	SF	8	4		1781	88/5200	Solex Keihin II.	81,0	86,4	5W-40 vagy 10W-40	min. 7bar, norm. 9-12bar			18 fok
Audi 80 1.8	1986-1991	RU	8	4		1781	75	Solex Keihin II.	81,0	86,4	5W-40 vagy 10W-40	min. 7bar, norm. 9-12bar			18 fok
Audi 80 1.9D	1989-1991	1Y	8	4	127	1896	65	Bosch adagoló	79,5	95,5	5W-50 vagy 10W-60	min. 26bar, norm. 34bar			-
Audi 80 2.0	1987-1991	PS	10	5		1994	115	KE-Jetronic KAT	81,0	77,4	5W-40 vagy 10W-50	min. 8bar, norm. 10-14bar		95	18 fok
Audi 80 2.0	1988-1991	3A	8	4	113	1984	113	KE-Motronic	82,5	92,8	5W-40 vagy 10W-60	min. 7.5bar, norm. 10.5-13.5bar		95	7 fok
Audi 80 2.0	1988-1991	NM	10	5		1994	112	Hitachi	81,0	77,4	5W-40 vagy 10W-60	min. 8bar, norm. 10-14bar		95	?
Audi 80 2.0	1990-1991	AAD	8	4	168	1984	115/5400	KE-Motronic	82,5	92,8	5W-40 vagy 10W-60	min. 7.5bar, norm. 10.5-13.5bar		95	7 fok
Audi 80 2.0	1989-1991	6A	16	4	181	1984	137	KE-Motronic	82,5	92,8	5W-40 vagy 10W-60	min. 7.5bar, norm. 10-13bar		95	6 fok
Audi 80 2.3	1986-1991	KV	10	5		2309	136	K-Jetronic	82,5	86,4	10W-40	min. 8bar, norm. 10-14bar			18 fok
Audi 80 2.3	1987-1991	NG	10	5	186/4000	2309	137	KE3-Jetronic	82,5	86,4	5W-40 vagy 10W-50	min. 8bar, norm. 10-14bar		95	15 fok
Audi 80 2.3	1988-1991	7A	20	5	220	2309	170	Hitachi	82,5	86,4	5W-40 vagy 10W-60	min. 8bar, norm. 10-14bar			?
Audi 80/90 (B4)															
Audi 80 1.6	1990-1994	ABB	8	4	135/3200	1595	102/6000	K-Jetronic	81,0	77,4	5W-40 vagy 10W-50	min. 7.5bar, norm. 10-13bar	10,0:1	95	7 fok
Audi 80 1.9TD	1991-1995	AAZ	8	4	140/2200	1896	75/4400	Bosch adagoló	79,5	95,5	5W-50 vagy 10W-60	min. 26bar, norm. 34bar	22,5:1	dízel	-
Audi 80 1.9TDi	1991-1995	1Z	8	4	182/2300	1896	90/4000	Bosch adagoló	79,5	95,5	5W-50 vagy 10W-60	min. 19bar, norm. 25-31bar	21,0:1	dízel	-
Audi 80 2.0	1991-1995	ABK	8	4	166/3200	1984	116/5400	Digifant I.	82,5	92,8	5W-40 vagy 10W-50	min. 9bar, norm 11-16bar	10,4:1	95	7 fok
Audi 80 2.0	1991-1995	ABT	8	4	148/3000	1984	90/5400	Mono-Motronic	82,5	92,8	5W-40 vagy 10W-40	min. 7bar, norm. 9-12bar	8,9:1	95	6 fok
Audi 80 2.0	1992-1995	ACE	16	4	181/4500	1984	140/5900	KE-Motronic	82,5	92,8	5W-40 vagy 10W-60	min. 7.5bar, norm. 10-13bar	10,8:1	95	7 fok
Audi 80 2.6	1992-1995	ABC	24	V6	225/3500	2598	150/5750	Hella	82,5	81,0	5W-40 vagy 10W-60	min. 9bar, norm 11-16bar	10,0:1	95	7 fok
Audi 80 2.8	1991-1995	AAH	24	V6	250/3000	2771	175/5500	Hitachi	82,5	86,4	5W-40 vagy 10W-50	min. 9bar, norm 11-16bar	10,3:1	95	?
Audi 80 S2	1990-1995	3B	20	5	309/1950	2226	220/5700	Mono-Motronic	81	86,4	5W-40 vagy 10W-60	min. 7bar, norm. 9-13bar	9,3:1	98	12 fok
Audi 80 S2	1993-1995	ABY	20	5	350/1950	2226	230/5900	Motronic	81	86,4	10W-60	min. 7bar, norm. 9-13bar	9,3:1	98	?
Audi RS2	1994-1995	ADU	20	5	410/3000	2226	320/6500	Motronic	81,0	86,4	10W-60		9,0:1	98	
Audi 100/200 (C3)															
Audi 100 1.8	1982-1991	DS	8	4		1781	90	Pierburg 2E2	81,0	86,4	5W-40 vagy 10W-50	min. 7bar, norm. 10-14bar	10,0:1	98	18 fok
Audi 100 1.8	1982-1987	DR	8	4		1781	75	Solex 1B3	81,0	86,4	10W-40	min. 7bar, norm. 10-12bar	8,5:1	95	18 fok
Audi 100 2.0	1984-1987	KP	10	5	170/3000	1994	116/5200	K-Jetronic	81,0	77,4	10W-40 vagy 10W-50	min. 9bar, norm 11-16bar	10,0:1	98	19 fok
Audi 100 2.3	1984-1987	HX	10	5	185/3500	2226	138/5700	K-Jetronic	81,0	86,4	10W-50	min. 9bar, norm 11-16bar	10,0:1	98	
2.2T	1983-1988	KG	10	5	252/3500	2144	182/5700	K-Jetronic	79,5	86,4	10W-50	min. 8.5bar, norm 9-13bar	8,8:1	98	
2.2	1984-1990	KU	10	5	185/3500	2226	138/5700	K-Jetronic	81,0	86,4	10W-50	min. 9bar, norm 11-16bar	10,0:1	98	
2.2	1984-1986	KZ	10	5	165/2500	2226	115/5500	KE-Jetronic	81,0	86,4	10W-50	min. 6.5bar, norm 8.5-12bar	8,5:1	91	
2.2T	1985-1990	MC	10	5	240/3000	2226	165/5500	K-Jetronic	81,0	86,4	10W-50	min. 6.5bar, norm 8-11bar	7,8:1	95	
2.3E	1985-1990	NF	10	5	190/4000	2309	136/5600	KE3-Jetronic	82,5	86,4	10W-50	min. 9bar, norm 11-16bar	10,0:1	95	16 fok
2.2	1985-1988	PX	10	5	172/3400	2226	120/5600	KE-Jetronic	81,0	86,4	10W-50	min. 6.5bar, norm 8.5-12bar	8,5:1	91	
2.0	1988-1990	RT	10	5	172/4000	1994	115/5400	KE-Jetronic	81,0	77,4	10W-50	min. 9bar, norm 11-16bar	10,0:1	95	
2.0	1986-1987	SL	10	5	165/3000	1994	113/5200	K-Jetronic	81,0	77,4	10W-50	min. 9bar, norm 11-16bar	10,0:1	95	
2.2	1982-1984	WC	10	5	180/4800	2144	136/5700	K-Jetronic	79,5	86,4	10W-50	min. 9bar, norm 11-16bar	10,0:1	98	18 fok
1.9	1982-1984	WH	10	5	150/3200	1921	100/5600	Keihin	79,5	77,4	10W-50	min. 9bar, norm 11-16bar	10,0:1	98	18 fok

Típus adatok

2.2	1983-1986	WU	10	5	152/3000	2144	105/5500	K-Jetronic	79,5	86,4	10W-50	min. 6.5bar, norm 8.5-12bar	8,2:1	91	
2.2T	1983-1986	KH	10	5	202/2500	2144	141/5500	K-Jetronic	79,5	86,4	10W-50	min. 6.5bar, norm 8.5-12bar	8,3:1	91	
2.2T	1988-1990	1B		5	270/3000	2226	200/5800	K-Jetronic	81,0	86,4	10W-60	min. 8.5bar, norm 9-13bar	8,6:1	98	
2.2T	1988-1990	2B		5	270/3000	2226	190/5800	K-Jetronic	81,0	86,4	10W-60	min. 8.5bar, norm 9-13bar	8,6:1	98	
2.2T	1988-1990	3B	20	5	309/1950	2226	220/5700	Motronic	81,0	86,4	10W-60	min. 7bar, norm. 9-13bar	9,3:1	95	12 fok
2.0D	1982-1990	CN	10	5	123/2800	1986	69/4800	Bosch VE szivattyú	76,5	86,4	5W-50 vagy 10W-60	min. 26bar, norm. 34bar	23,0:1	dízel	-
2.0TD	1982-1990	DE	10	5	172/2800	1986	87/4500	Bosch VE szivattyú	76,5	86,4	5W-50 vagy 10W-60	min. 26bar, norm. 34bar	23,0:1	dízel	-
2.0TD	1988-1990	NC	10	5	192/2200	1986	100/4500	Bosch VE szivattyú	76,5	86,4	5W-50 vagy 10W-60	min. 26bar, norm. 34bar	23,0:1	dízel	-
2.4D	1989-1990	3D	10	5	164/2400	2370	82/4400	Bosch VE szivattyú	79,5	95,5	5W-50 vagy 10W-60	min. 26bar, norm. 34bar	22,5:1	dízel	-
2.5TD	1990	1T	10	5	265/2250	2461	120/4250	Bosch VE 5/11E	81,0	95,5	5W-50 vagy 10W-60	min. 24bar, norm 30bar	20,5:1	dízel	-
3.6 V8	1990-1992	PT	32	V8	340/4000	3562	250/5800	Motronic M2.4	81,0	86,4	10W-50	min. 7,5bar, norm 10-13bar	10,6:1	95	7 fok
4.2 V8	1992-1993	ABH	32	V8	400/4000	4172	280/5800	Motronic M2.4.1	84,5	93,04	10W-50	min. 7,5bar, norm 10-13bar	10,6:1	95	7 fok
2.2 (svájc)	1982-1984	KF	10	5	168/5000	2144	130/5750	K-Jetronic	79,5	86,4	10W-40	min. 9bar, norm 11-16bar	9,3:1	95	-3 fok
Transporter (T4)															
2.0	1990-1996	AAC	8	4	159/2000	1968	84/4300	Digifant	81,0	95,5	10W-40	min. 7bar, norm 9-12bar	8,5:1	91	
2.5	1990-1994	AAF	10	5	200/2200	2461	115/4500	Digifant	81,0	95,5	10W-40	min. 7bar, norm 9-12bar	8,5:1	91	6 fok
2.4D	1990-1998	AAB	10	5	164/1800	2370	78/3700	Bosch VE 5/8 F2100	79,5	95,5	5W-50	min. 26bar, norm. 34bar	22,5:1	dízel	
Audi quattro															
quattro	1980-1987		10	5	285/3500	2144	200/5500		79,5	86,4			7,0:1	98	
quattro	1987-1989		10	5	270/3000	2226	200/5500		81,0	86,4			8,6:1	98	
quattro 20V	1989-1991		20	5	309/1950	2226	220/5900	Motronic	81,0	86,4			9,3:1	98	
sport quattro	1984-1986		10	5	351/3700	2133	306/6700		79,3	86,4				98	
S1	1985-1986		20	5	480/5500	2133	450/7500		79,3	86,4				98	
Audi 80 (B2)															
1.6		WP,YU	8	4		1588		?	79,5	80,0	10W-40	min. 7bar, norm 9-12bar	7,0:1		
1.7		WT	8	4		1715		?	79,5	86,4	10W-40	min. 7bar, norm 9-12bar	8,2:1		
1.6GLE	1979-1982	YZ	8	4		1588	110/5500	K-Jetronic	79,5	80,0	10W-40	min. 7bar, norm 9-12bar	9,5:1		
1.6	1979-1983	YG,YH	8	4	122/3200	1588	85/5600	?	79,5	80,0	10W-40	min. 7bar, norm 9-12bar	8,2:1		
1.9	1981-1983	WN	10	5	154/3700	1921	115/5900	Zenith 2B5	79,5	77,4	10W-40	min. 8bar, norm. 10-14bar	10,0:1	98	
2.2	1979-1984	WE	10	5		2144		K-Jetronic	79,5	86,4	10W-40	min. 7bar, norm 9-12bar	8,0:1		
1.6	1984-1986	DT	8	4	125/2700	1595	75/5200	Pierburg 2E2	81,0	77,4	10W-40	min. 7bar, norm 9-12bar	9,0:1	95	9 fok
1.6	1984-1986	WV	8	4	122/3200	1588	85/5600	?	79,5	80,0	10W-40	min. 7,5bar, norm 10-13bar	8,2:1		18 fok
1.8		DD	8	4	138/2500	1781	75/4500	?	81,0	86,4	10W-40	min. 7bar, norm 9-12bar	8,8:1		18 fok
1.8		DS	8	4	145/3300	1781	90/5200	?	81,0	86,4	10W-40	min. 7,5bar, norm 10-13bar	10,0:1		18 fok
1.8GTE		DZ	8	4	160/3400	1781	112/5800	K-Jetronic	81,0	86,4	10W-40	min. 7,5bar, norm 10-13bar	10,0:1		6 fok
1.8		NE	8	4		1781		Keihin	81,0	86,4	10W-40	min. 7,5bar, norm 10-13bar	10,0:1		18 fok
2.0	1983-1984	JS	10	5	165/3200	1994	115/5400	K-Jetronic	81,0	77,4	10W-40	min. 7,5bar, norm 10-13bar	10,0:1		18 fok
2.0		SK	10	5		1994		K-Jetronic	81,0	77,4	10W-40	min. 7,5bar, norm 10-13bar	10,0:1		
2,2		KE	10	5	176/4500	2144	136/5900	K-Jetronic	79,5	86,4	10W-40	min. 8bar, norm. 10-14bar	9,3:1		6 fok
2,2		KK	10	5	171/4800	2144	130/5900	K-Jetronic	79,5	86,4	10W-40	min. 8bar, norm. 10-14bar	9,3:1		18 fok
2,3		KV	10	5		2226		K-Jetronic	81,0	86,4	10W-40	min. 8bar, norm. 10-14bar	10,0:1		19 fok
1,3		?	8	4	90/3400	1272	55/5800	?	75,0	72,0	10W-40		8,2:1		
1,3		?	8	4	100/3500	1296	60/5600	?	75,0	73,4	10W-40		8,2:1		
Golf II.															
1,3	1989-1991	NZ	8	4		1272	55	Digijet			10W-40				
1.3GT	1984-1987	GT	8	4		1272	58	Solex Pict			10W-40				
1.3GT	1983-1991	HK	8	4		1272	55	Pierburg 2E3			10W-40				
1,6	1983-1989	RF	8	4		1595	75	Pierburg 2E2	81,0	77,4	10W-40				
1,6	1986-1991	PN	8	4		1595	70	Pierburg 2EE	81,0	77,4	10W-40				
1.8 16V	1985-1991	PL	16	4		1781	130	KE-Jetronic	81,0	86,4	10W-40				
1.8 16V	1986-1991	KR	16	4		1781	138	K-Jetronic	81,0	86,4	10W-40				

Típus adatok

LT														
2.4TD		DV		6		2383	102							
Transporter (T3)														
2.1i		DJ		4		2109	110							
Passat II.														
1,6	1984-1988	DT	8	4	125	1595	75	Pierburg 2E2	81,0	77,4	10W-40			
1,8	1984-1988	DS/JN	8	4	145	1781	90	Pierburg 2E2	81,0	86,4	10W-40			
2.0i	1984-1986	JS	10	5	165	1994	115	K-Jetronic	81,0	77,4	10W-40			
Passat III.														
1.9TDi	1993-1996	1Z	8	4	182	1896	90	Bosch TDI						
1,6	1994-1997	AEK/AFT		4		1595	101	Motornic M2.9						

